



REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE
V0	--	/		2021.06.25

IEC 技术参数		IEC61076-2-105
IEC Technical Data		
工作温度 Operating temperatur [°C]		-25~+80
防护等级 IP Class (IN Locked condition)		IP67
额定电压 Rated Voltage [V]		60
额定电流 Rated Current [A]		1
导线截面积Conductor cross section 硬质/柔性导线 Solid/ flexible [mm²]		/
接线范围 Wire Range 单/多芯线 Solid/Stranded [AWG]		PCB
材料 Material		
绝缘材料 Insulation Material		PA 66
阻燃等级 Imflammability		UL94V-0
导体材料 Contactor Material		铜合金 Copper alloy
导体镀层 Contactive Coating		镀金 Gold Plated
螺母/螺丝 Connector Nut/Screw		Brass With Nickel Plated 铜镀镍
符合RoHS环保要求		

Contacts Pin 数	3Pin	4Pin
Coding 编码	A-Coding	A-Coding
Rated Current 额定电流	1A	1A
Rated Voltage 额定电压	60V	60V
Wire Range 线范围	26AWG	26AWG
PART NO. 品名:	M05-A03-ST0-F01-BQ2	M05-A04-ST0-F01-BQ2
Customized. 定制化:



3Pin 4Pin
PCB Layout



Panel cut-out

编号 No.	料号 Materials.No	品名 Name	材料规格 Description	单位 Unit	用量 Qty
G	O-Ring	O-Ring FKM Black		pcs	1
F	O-Ring	O-Ring FKM Black		pcs	1
E	Resin	Black epoxy resin for sealing		g	1
D	Nut	Nut:M7X0.75,Brass With Nickel Plated		pcs	1
C	Housing	A-Coding Female,Black PA66		pcs	1
B	Terminal	Female Terminal ,Brass With Gold Plated		pcs	X
A	Screw	Screw M5X0.5,Brass With Nickel Plated		pcs	1


NO SPECIFIED TOLERANCE		Cus' P/N:	Order No.:	---	Drawing No.:	SP-02-M000XX
LINEAR	0.5-6	±0.1	DES.	JUN	DATE	UNITS mm
	6-30	±0.2	CHK.	DATE	SIZE	A4
	>30	±2%	APP.	DATE	SCALE	X:X
ANGLES	±1°				文件等级: 外部公开	



慈溪市万捷电子有限公司
CIXI WANJIE ELECTRONIC CO., LTD

PART NO.:
M05-AXXP-ST0-F01-BQ2

THIRD ANGLE PROJECTION



1 of 1